

SECTION 10B

TOILET ACCESSORIES

1. APPLICABLE PUBLICATIONS: The Federal Specification (Fed. Spec.) listed below, forms a part of this specification to the extent referenced. The publication is referred to in the text by basic designation only.

WW-P-541/8A & Am-1	Plumbing Fixtures (Accessories, Land Use) (Detail Specification)
-----------------------	---

2. GENERAL REQUIREMENTS: Toilet accessories as specified herein shall be provided where indicated in accordance with the SCHEDULE hereinafter. Each accessory item shall be complete with the necessary mounting plates, anchors, and fasteners. Concealed mounting plates shall be of sturdy construction with corrosion resistant surface.

3. SAMPLES AND DESCRIPTIVE DATA: One sample of each accessory proposed for use shall be submitted for approval. Samples shall be accompanied by descriptive data indicating materials of construction, fasteners proposed for use for each type of wall construction, and mounting instructions. Approved samples may be incorporated into the finished work provided they are identified and their locations noted.

4. ANCHORS AND FASTENERS shall be capable of developing a restraining force commensurate with the strength of the accessory to be mounted and shall be well suited for use with the supporting construction. Where exposed fasteners are permitted, they shall have oval heads and finish to match the accessory, except exposed fasteners in all locations shall be of tamper-proof design.

5. FINISHES: Finishes on metal shall be provided as follows:

<u>Metal</u>	<u>Finish</u>
Stainless steel	No. 4 general-purpose polished
Carbon steel, copper alloy, and brass	Chromium plated, bright

6. ACCESSORY ITEMS shall conform to the respective specification and other requirements specified below.

6.1 Paper Towel Dispenser (PTD): Paper towel dispenser shall conform to Fed. Spec. WW-P-541, Type I, Class 3, Mounting R, Style P. Dispenser shall have towel compartment and utility shelf behind mirror door with one liquid soap dispenser and shelf. Capacity of dispensers shall be 400 C-fold or 700 multi-fold towels.

6.2 Sanitary Napkin and Tampon Disposer (SND): Sanitary napkin and tampon disposer shall conform to Fed. Spec. WW-P-541, Type II, Mounting P, stainless steel. Reusable liner of the type standard with the manufacturer shall be provided.

6.3 Sanitary Napkin and Tampon Dispenser (SNTD): Sanitary napkin and tampon dispenser shall conform to Fed. Spec. WW-P-541, Type I, Class 5, surface mounted. Dispenser, including door shall be stainless steel and have a capacity of 15 napkins and 22 tampons. Dispensing mechanism shall be for complimentary operation.

6.4 Toilet Tissue Dispenser (TTD): Toilet tissue dispenser shall conform to Fed. Spec. WW-P-541, Type I, Class 1, Style A, stainless steel.

6.5 Waste Receptacle (WR): Waste receptacle shall conform to Fed. Spec. WW-P-541, Type II, stainless steel, designed for semirecessed mounting. Reuseable liner, of the type standard with the receptacle manufacturer, shall be provided. Capacity shall be not less than 8.5 cubic feet.

7. INSTALLATION: Toilet accessories shall be securely fastened to the supporting construction in accordance with the approved submittals. Accessories shall be protected from damage from the time of installation until acceptance.

8. SCHEDULE:

<u>Room or Space</u>	<u>Acces- sories Required WR</u>	<u>Acces- sories Required PTD</u>	<u>Acces- sories Required SND</u>	<u>Acces- sories Required SNTD</u>	<u>Acces- sories Required TTD</u>
125	1	3	0	0	2
123	1	2	2	1	2